Introduction to Robotics Mechanics and Control 4th edition Craig Solutions Manual

SKU: 9780133489798-SOLUTIONS

Chapter 2 Solutions for Introduction to Robotics

1. a) Use (2.3) to obtain

$$ {}^A_B R = \begin{bmatrix} 1 & 0 & 0 \\ 0 & 0 & 1 \\ 0 & -1 & 0 \end{bmatrix} $$

b) Use (2.74) to get

$$ \alpha = 90 \text{ degrees} $$
$$ \beta = 90 \text{ degrees} $$
$$ \gamma = -90 \text{ degrees} $$

2. a) Use (2.64) to obtain

$$ {}^A_B R = \begin{bmatrix} .330 & -.770 & .547 \\ .908 & .418 & .0396 \\ -.259 & .483 & .837 \end{bmatrix} $$

b) Answer is the same as in (a) according to (2.71)

3. Use (2.19) to obtain the transformation matrices. The rotation is X-Y-Z fixed angles, so use (2.64) for that 3×3 submatrix, with angles

$$ \gamma = 0 \text{ degrees} $$
$$ \beta = -\sin^{-1}\left(\frac{\text{tripod_height}}{\text{distance_along_optical_axis}}\right) = -\sin^{-1}\left(\frac{1.5}{5}\right) = -107 \text{ degrees} $$
$$ \alpha_C = 0 \text{ degrees} $$
$$ \alpha_D = 120 \text{ degrees} $$
$$ \alpha_E = 240 \text{ degrees} $$

The position vectors to the camera-frame origins are

This work is protected by United States copyright laws and is provided solely for the use of instructors in teaching their courses and assessing student learning. Dissemination or sale of any part of this work (including on the World Wide Web) will destroy the integrity of the work and is not permitted.

© 2018 Pearson Education, Inc., Hoboken, NJ. All rights reserved. This material is protected under all copyright laws as they currently exist. No portion of this material may be reproduced, in any form or by any means, without permission in writing from the publisher.

Introduction to Robotics Mechanics and Control 4th edition Craig Solutions Manual

$$
{}^{B}P_{CORG} = \begin{bmatrix} \text{horizontal_distance} \\ 0 \\ \text{tripod_height} \end{bmatrix} = \begin{bmatrix} 4.77 \\ 0 \\ 1.50 \end{bmatrix}
$$

$$
{}^{B}P_{DORG} = \begin{bmatrix} \text{horizontal_distance} \times \cos\alpha_D \\ \text{horizontal_distance} \times \sin\alpha_D \\ \text{tripod_height} \end{bmatrix} = \begin{bmatrix} -2.39 \\ 4.13 \\ 1.5 \end{bmatrix}
$$

$$
{}^{B}P_{EORG} = \begin{bmatrix} \text{horizontal_distance} \times \cos\alpha_E \\ \text{horizontal_distance} \times \sin\alpha_E \\ \text{tripod_height} \end{bmatrix} = \begin{bmatrix} -2.38 \\ -4.13 \\ 1.50 \end{bmatrix},
$$

where $\text{horizontal_distance} = \sqrt{(\text{distance_along_optical_axis})^2 - (\text{tripod_height})^2}$.
Combining the rotation and translation yields the transformation matrices via (2.19) as

$$
{}^{B}_{C}T = \begin{bmatrix} -.300 & 0 & -.954 & 4.77 \\ 0 & 1.00 & 0 & 0 \\ .954 & 0 & -.300 & 1.50 \\ 0 & 0 & 0 & 1 \end{bmatrix}
$$

$$
{}^{B}_{D}T = \begin{bmatrix} .150 & -.866 & .477 & -2.39 \\ -.260 & -.500 & -.826 & 4.13 \\ .954 & 0 & -.300 & 1.50 \\ 0 & 0 & 0 & 1 \end{bmatrix}
$$

$$
{}^{B}_{E}T = \begin{bmatrix} .150 & .866 & .477 & -2.39 \\ .260 & -.500 & .826 & -4.13 \\ .954 & 0 & -.300 & 1.50 \\ 0 & 0 & 0 & 1 \end{bmatrix}
$$

This work is protected by United States copyright laws and is provided solely for the use of instructors in teaching their courses and assessing student learning. Dissemination or sale of any part of this work (including on the World Wide Web) will destroy the integrity of the work and is not permitted.

4. The camera-frame origin is located at ${}^{B}P_{CORG} = [7 \quad -2 \quad 5]^{\mathsf{T}}$. Use (2.19) to get the transformation, ${}^{B}_{C}T$. The rotation is Z-Y-X Euler angles, so use (2.71) with

$$
\begin{aligned}
&\alpha = 0 \text{ degrees} \\
&\beta = -110 \text{ degrees} \\
&\gamma = -20 \text{ degrees}
\end{aligned}
$$

to get

$$
{}^{B}_{C}T = \begin{bmatrix} -.342 & .321 & -.883 & 7.00 \\ 0 & .940 & .342 & -2.00 \\ .940 & .117 & -.321 & 5.00 \\ 0 & 0 & 0 & 1 \end{bmatrix}
$$

© 2018 Pearson Education, Inc., Hoboken, NJ. All rights reserved. This material is protected under all copyright laws as they currently exist. No portion of this material may be reproduced, in any form or by any means, without permission in writing from the publisher.
Introduction to Robotics Mechanics and Control 4th edition Craig Solutions Manual

5. Let

$$^{B}P_1 = {}^{B}P_0 + 5\,{}^{B}V_0 = [9.5 \quad 1.00 \quad -1.50]^{\mathsf{T}}$$

The object's position in $\{A\}$ is

$$^{A}P_1 = {}^{A}_{B}T\,{}^{B}P_1 = [-4.89 \quad 2.11 \quad 3.60]^{\mathsf{T}}$$

6. *(2.1)*

$$\begin{aligned} R &= \mathrm{rot}(\hat{Y}, \phi)\,\mathrm{rot}(\hat{Z}, \theta) \\ &= \begin{bmatrix} c\phi & 0 & s\phi \\ 0 & 1 & 0 \\ -s\phi & 0 & c\phi \end{bmatrix} \begin{bmatrix} c\theta & -s\theta & 0 \\ s\theta & c\theta & 0 \\ 0 & 0 & 1 \end{bmatrix} \\ &= \begin{bmatrix} c\phi\,c\theta & -c\phi\,s\theta & s\phi \\ s\theta & c\theta & 0 \\ -s\phi\,c\theta & s\phi\,s\theta & c\phi \end{bmatrix} \end{aligned}$$

7. *(2.2)*

$$\begin{aligned} R &= \mathrm{rot}(\hat{X}, 60)\,\mathrm{rot}(\hat{Y}, -45) \\ &= \begin{bmatrix} 1 & 0 & 0 \\ 0 & .500 & -.866 \\ 0 & .866 & .500 \end{bmatrix} \begin{bmatrix} .707 & 0 & -.707 \\ 0 & 1 & 0 \\ .707 & 0 & .707 \end{bmatrix} \\ &= \begin{bmatrix} .707 & 0 & -.707 \\ -.612 & .500 & -.612 \\ .353 & .866 & .353 \end{bmatrix} \end{aligned}$$

This work is protected by United States copyright laws and is provided solely for the use of instructors in teaching their courses and assessing student learning. Dissemination or sale of any part of this work (including on the World Wide Web) will destroy the integrity of the work and is not permitted.

8. *(2.12)* Velocity is a "free vector" and only will be affected by rotation, and not by translation:

$$\begin{aligned} {}^{A}V = {}^{A}_{B}R\,{}^{B}V &= \begin{bmatrix} .707 & 0 & -.707 \\ -.612 & .500 & -.612 \\ .353 & .866 & .353 \end{bmatrix} \begin{bmatrix} 30.0 \\ 40.0 \\ 50.0 \end{bmatrix} \\ &= [-14.1 \quad -29.0 \quad 62.9]^{\mathsf{T}} \end{aligned}$$

9. *(2.31)*

$${}^{C}_{B}T = \begin{bmatrix} 0 & 0 & -1 & 2 \\ .500 & -.866 & 0 & 0 \\ -.866 & -.500 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

10. *(2.37)* Using (2.45) we get that

$$^{B}P_{AORG} = -{}^{A}_{B}R^{\mathsf{T}}\,{}^{A}P_{AORG} = -\begin{bmatrix} .25 & .87 & .43 \\ .43 & -.50 & .75 \\ .86 & .00 & -.50 \end{bmatrix} \begin{bmatrix} 5.0 \\ -4.0 \\ 3.0 \end{bmatrix} = \begin{bmatrix} .94 \\ -6.4 \\ -2.8 \end{bmatrix}$$

© 2018 Pearson Education, Inc., Hoboken, NJ. All rights reserved. This material is protected under all copyright laws as they currently exist. No portion of this material may be reproduced, in any form or by any means, without permission in writing from the publisher.