Power System Analysis and Design 6th edition Glover Solutions Manual

SKU: 9781305632134-SOLUTIONS

Chapter 2
Fundamentals

ANSWERS TO MULTIPLE-CHOICE TYPE QUESTIONS

2.1 b
2.2 a
2.3 c
2.4 a
2.5 b
2.6 c
2.7 a
2.8 c
2.9 a
2.10 c
2.11 a
2.12 b
2.13 b
2.14 c
2.15 a
2.16 b
2.17 A. a
B. b
C. a
2.18 c
2.19 a
2.20 A. c
B. a
C. b
2.21 a
2.22 a
2.23 b
2.24 a
2.25 a
2.26 b
2.27 a
2.28 b
2.29 a
2.30 (i) c
(ii) b
(iii) a
(iv) d
2.31 a
2.32 a

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

2.1 (a) $\bar{A}_1 = 6\angle 30° = 6\left[\cos 30° + j\sin 30°\right] = 5.20 + j\,3$

(b) $\bar{A}_2 = -4 + j5 = \sqrt{16+25}\,\angle \tan^{-1}\dfrac{5}{-4} = 6.40\angle 128.66° = 6.40e^{j128.66°}$

(c) $\bar{A}_3 = (5.20 + j3) + (-4 + j5) = 1.20 + j8 = 8.01\angle 81.50°$

(d) $\bar{A}_4 = (6\angle 30°)(6.40\angle 128.66°) = 38.414\angle 158.658° = -35.78 + j13.98$

(e) $\bar{A}_5 = (6\angle 30°)/(6.40\angle -128.66°) = 0.94\angle 158.66° = 0.94e^{j158.66°}$

2.2 (a) $\bar{I} = 500\angle -30° = 433.01 - j250$

(b) $i(t) = 4\sin(\omega t + 30°) = 4\cos(\omega t + 30° - 90°) = 4\cos(\omega t - 60°)$

$\bar{I} = (4)\angle -60° = 2.83\angle -60° = 1.42 - j2.45$

(c) $\bar{I} = (5/\sqrt{2})\angle -15° + 4\angle -60° = (3.42 - j0.92) + (2 - j3.46)$

$= 5.42 - j\,4.38 = 6.964\angle -38.94°$

2.3 (a) $V_{max} = 400\,\text{V};\ I_{max} = 100\,\text{A}$

(b) $V = 400/\sqrt{2} = 282.84\,\text{V};\ I = 100/\sqrt{2} = 70.71\,\text{A}$


(c) $\bar{V} = 282.84\angle 30°\,\text{V};\ \bar{I} = 70.71\angle -80°\,\text{A}$

2.4 (a) $\bar{I}_1 = 10\angle 0°\dfrac{-j6}{8 + j6 - j6} = 10\dfrac{6\angle -90°}{8} = 7.5\angle -90°\,\text{A}$

$\bar{I}_2 = \bar{I} - \bar{I}_1 = 10\angle 0° - 7.3\angle -90° = 10 + j7.5 = 12.5\angle 36.87°\,\text{A}$

$\bar{V} = \bar{I}_2(-j6) = (12.5\angle 36.87°)(6\angle -90°) = 75\angle -53.13°\,\text{V}$

(b)



2.5 (a) $\upsilon(t) = 277\sqrt{2}\cos(\omega t + 30°) = 391.7\cos(\omega t + 30°)\,\text{V}$

(b) $\bar{I} = \bar{V}/20 = 13.85\angle 30°\,\text{A}$

$i(t) = 19.58\cos(\omega t + 30°)\,\text{A}$

(c) $\bar{Z} = j\omega L = j(2\pi 60)(10\times 10^{-3}) = 3.771\angle 90°\,\Omega$

$\bar{I} = \bar{V}/\bar{Z} = (277\angle 30°)/(3.771\angle 90°) = 73.46\angle -60°\,\text{A}$

$i(t) = 73.46\sqrt{2}\cos(\omega t - 60°) = 103.9\cos(\omega t - 60°)\,\text{A}$

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

(d) $\bar{Z} = -j25\ \Omega$

$\bar{I} = \bar{V}/\bar{Z} = (277\angle 30°)/(25\angle -90°) = 11.08\angle 120°\ \text{A}$

$i(t) = 11.08\sqrt{2}\cos(\omega t + 120°) = 15.67\cos(\omega t + 120°)\ \text{A}$

2.6 (a) $\bar{V} = \left(75/\sqrt{2}\right)\angle -15° = 53.03\angle -15°$; ω does not appear in the answer.

(b) $v(t) = 50\sqrt{2}\cos(\omega t + 10°)$; with $\omega = 377$,


$v(t) = 70.71\cos(377t + 10°)$

(c) $\bar{A} = A\angle\alpha;\ \bar{B} = B\angle\beta;\ \bar{C} = \bar{A} + \bar{B}$

$c(t) = a(t) + b(t) = \sqrt{2}\ \text{Re}\left[\bar{C}e^{j\omega t}\right]$

The resultant has the same frequency ω.

2.7 (a) The circuit diagram is shown below:



(b) $\bar{Z} = 3 + j8 - j4 = 3 + j4 = 5\angle 53.1°\ \Omega$

(c) $\bar{I} = (100\angle 0°)/(5\angle 53.1°) = 20\angle -53.1°\ \text{A}$

The current lags the source voltage by 53.1°

Power Factor $= \cos 53.1° = 0.6$ Lagging

2.8 $\bar{Z}_{LT} = j(377)(30.6\times 10^{-6}) = j11.536\ \text{m}\Omega$

$\bar{Z}_{LL} = j(377)(5\times 10^{-3}) = j1.885\ \Omega$


$$\bar{Z}_C = -j\frac{1}{(377)(921\times 10^{-6})} = -j2.88\ \Omega$$

$$\bar{V} = \frac{120\sqrt{2}}{\sqrt{2}}\angle -30°\ \text{V}$$

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

The circuit transformed to phasor domain is shown below:



2.9 $KVL:\ 120\angle 0^\circ = (60\angle 0^\circ)(0.1 + j0.5) + \bar{V}_{LOAD}$

$$\therefore\ \bar{V}_{LOAD} = 120\angle 0^\circ - (60\angle 0^\circ)(0.1 + j0.5)$$
$$= 114.1 - j30.0 = 117.9\angle -14.7^\circ \text{ V} \ \leftarrow$$

2.10 (a) $p(t) = v(t)i(t) = \left[400\cos(\omega t + 30^\circ)\right]\left[100\cos(\omega t - 80^\circ)\right]$

$$= \frac{1}{2}(400)(100)\left[\cos 110^\circ + \cos(2\omega t - 50^\circ)\right]$$
$$= -6840.4 + 2\times 10^4 \cos(2\omega t - 50^\circ)\text{ W}$$

(b) $P = VI\cos(\delta - \beta) = (282.84)(70.71)\cos(30^\circ + 80^\circ)$

$= -6840$ W Absorbed

$= +6840$ W Delivered

(c) $Q = VI\sin(\delta - \beta) = (282.84)(70.71)\sin 110^\circ$

$= 18.79$ kVAR Absorbed

(d) The phasor current $(-\bar{I}) = 70.71\angle -80^\circ + 180^\circ = 70.71\angle 100^\circ$ A leaves the positive terminal of the generator.

The generator power factor is then $\cos(30^\circ - 100^\circ) = 0.3420$ leading

2.11 (a) $p(t) = v(t)i(t) = 391.7\times 19.58\cos^2(\omega t + 30^\circ)$

$$= 0.7669\times 10^4\left(\frac{1}{2}\right)\left[1 + \cos(2\omega t + 60^\circ)\right]$$
$$= 3.834\times 10^3 + 3.834\times 10^3\cos(2\omega t + 60^\circ)\text{ W}$$
$$P = VI\cos(\delta - \beta) = 277\times 13.85\cos 0^\circ = 3.836\text{ kW}$$
$$Q = VI\sin(\delta - \beta) = 0\text{ VAR}$$

Source Power Factor $= \cos(\delta - \beta) = \cos(30^\circ - 30^\circ) = 1.0$

(b) $p(t) = v(t)i(t) = 391.7\times 103.9\cos(\omega t + 30^\circ)\cos(\omega t - 60^\circ)$

$$= 4.07\times 10^4\left(\frac{1}{2}\right)\left[\cos 90^\circ + \cos(2\omega t - 30^\circ)\right]$$
$$= 2.035\times 10^4\cos(2\omega t - 30^\circ)\text{ W}$$
$$P = VI\cos(\delta - \beta) = 277\times 73.46\cos(30^\circ + 60^\circ) = 0\text{ W}$$
$$Q = VI\sin(\delta - \beta) = 277\times 73.46\sin 90^\circ = 20.35\text{ kVAR}$$
$$pf = \cos(\delta - \beta) = 0\text{ Lagging}$$

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

(c) $p(t) = \upsilon(t)i(t) = 391.7 \times 15.67 \cos(\omega t + 30°)\cos(\omega t + 120°)$

$= 6.138 \times 10^3 \left(\frac{1}{2}\right)\left[\cos(-90°) + \cos(2\omega t + 150°)\right] = 3.069 \times 10^3 \cos(2\omega t + 150°)\,\text{W}$

$P = VI\cos(\delta - \beta) = 277 \times 11.08 \cos(30° - 120°) = 0\,\text{W}$

$Q = VI\sin(\delta - \beta) = 277 \times 11.08 \sin(-90°)$

$= -3.069\,\text{kVAR}$ Absorbed $= +3.069\,\text{kVAR}$ Delivered

$pf = \cos(\delta - \beta) = \cos(-90°) = 0$ Leading

2.12 (a) $p_R(t) = (359.3\cos\omega t)(35.93\cos\omega t)$

$= 6455 + 6455\cos 2\omega t\ \text{W}$

(b) $p_x(t) = (359.3\cos\omega t)\left[14.37\cos(\omega t + 90°)\right]$

$= 2582\cos(2\cot + 90°)$

$= -2582\sin 2\omega t\ \text{W}$

(c) $P = V^2/R = \left(359.3/\sqrt{2}\right)^2 /10 = 6455\,\text{W}$ Absorbed

(d) $Q = V^2/X = \left(359.3/\sqrt{2}\right)^2 /25 = 2582\,\text{VARS}$ Delivered

(e) $(\beta - \delta) = \tan^{-1}(Q/P) = \tan^{-1}(2582/6455) = 21.8°$

Power factor $= \cos(\delta - \beta) = \cos(21.8°) = 0.9285$ Leading

2.13 $\bar{Z} = R - jx_c = 10 - j25 = 26.93 \angle -68.2°\ \Omega$

$i(t) = (359.3/26.93)\cos(\omega t + 68.2°)$

$= 13.34\cos(\omega t + 68.2°)\,\text{A}$

(a) $p_R(t) = \left[13.34\cos(\omega t + 68.2°)\right]\left[133.4\cos(\omega t + 68.2°)\right]$

$= 889.8 + 889.8\cos\left[2(\omega t + 68.2°)\right]\text{W}$

(b) $p_x(t) = \left[13.34\cos(\omega t + 68.2°)\right]\left[333.5\cos(\omega t + 68.2° - 90°)\right]$

$= 2224\sin\left[2(\omega t + 68.2°)\right]\text{W}$

(c) $P = I^2R = \left(13.34/\sqrt{2}\right)^2 10 = 889.8\,\text{W}$

(d) $Q = I^2X = \left(13.34/\sqrt{2}\right)^2 25 = 2224\,\text{VARS}$

(e) $pf = \cos\left[\tan^{-1}(Q/P)\right] = \cos\left[\tan^{-1}(2224/889.8)\right]$

$= 0.3714$ Leading

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

2.14 (a) $\bar{I} = 2\angle 0°\,\text{kA}$

$$\bar{V} = \bar{Z}\,\bar{I} = (3\angle -45°)(2\angle 0°) = 6\angle -45°\,\text{kV}$$

$$\upsilon(t) = 6\sqrt{2}\cos(\omega t - 45°)\,\text{kV}$$

$$p(t) = \upsilon(t)i(t) = \left[6\sqrt{2}\cos(\omega t - 45°)\right]\left[2\sqrt{2}\cos\omega t\right]$$

$$= 24\left(\frac{1}{2}\right)\left[\cos(-45°) + \cos(2\omega t - 45°)\right]$$

$$= 8.49 + 12\cos(2\omega t - 45°)\,\text{MW}$$

(b) $P = VI\cos(\delta - \beta) = 6 \times 2\cos(-45° - 0°) = 8.49\,\text{MW}$ Delivered

(c) $Q = VI\sin(\delta - \beta) = 6 \times 2\sin(-45° - 0°)$

$= -8.49\,\text{MVAR}$ Delivered $= +8.49\,\text{MVAR}$ Absorbed

(d) $pf = \cos(\delta - \beta) = \cos(-45° - 0°) = 0.707$ Leading

2.15 (a) $\bar{I} = \left[\left(4/\sqrt{2}\right)\angle 60°\right] / (2\angle 30°) = \sqrt{2}\angle 30°\,\text{A}$


$$i(t) = 2\cos(\omega t + 30°)\,\text{A} \text{ with } \omega = 377\,\text{rad/s}$$

$$p(t) = \upsilon(t)i(t) = 4\left[\cos 30° + \cos(2\omega t + 90°)\right]$$

$$= 3.46 + 4\cos(2\omega t + 90°)\,\text{W}$$

(b) $\upsilon(t)$, $i(t)$, and $p(t)$ are plotted below.

(c) The instantaneous power has an average value of 3.46 W, and the frequency is twice that of the voltage or current.



© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

2.16 (a) $\bar{Z} = 10 + j120\pi \times 0.04 = 10 + j15.1 = 18.1\angle 56.4°\ \Omega$

$pf = \cos 56.4° = 0.553$ Lagging

(b) $\bar{V} = 120\angle 0°\ \text{V}$

The current supplied by the source is

$\bar{I} = (120\angle 0°)/(18.1\angle 56.4°) = 6.63\angle -56.4°\ \text{A}$

The real power absorbed by the load is given by

$P = 120 \times 6.63 \times \cos 56.4° = 440\ \text{W}$

which can be checked by $I^2R = (6.63)^2\, 10 = 440\ \text{W}$

The reactive power absorbed by the load is

$Q = 120 \times 6.63 \times \sin 36.4° = 663\ \text{VAR}$

(c) Peak Magnetic Energy $= W = LI^2 = 0.04(6.63)^2 = 1.76\ \text{J}$

$Q = \omega W = 377 \times 1.76 = 663\ \text{VAR}$ is satisfied.

2.17 (a) $\bar{S} = \bar{V}\bar{I}^* = \bar{Z}\bar{I}\bar{I}^* = \bar{Z}|\bar{I}|^2 = j\omega LI^2$

$Q = \text{Im}[\bar{S}] = \omega LI^2$ ←

(b) $\upsilon(t) = L\dfrac{di}{dt} = -\sqrt{2}\omega L\, I \sin(\omega t + \theta)$

$p(t) = \upsilon(t) \cdot i(t) = -2\omega L\, I^2 \sin(\omega t + \theta)\cos(\omega t + \theta)$

$= -\omega L\, I^2 \sin 2(\omega t + \theta)$ ←

$= -Q \sin 2(\omega t + \theta)$ ←

Average real power P supplied to the inductor $= 0$ ←

Instantaneous power supplied (to sustain the changing energy in the magnetic field) has a maximum value of Q. ←

2.18 (a) $\bar{S} = \bar{V}\bar{I}^* = \bar{Z}\bar{I}\bar{I}^* = \text{Re}\left[\bar{Z}I^2\right] + j\,\text{Im}\left[\bar{Z}I^2\right]$

$= P + jQ$

$\therefore P = |\bar{Z}|I^2 \cos\angle\bar{Z};\ Q = |\bar{Z}|I^2 \sin\angle\bar{Z}$ ←

(b) Choosing $i(t) = \sqrt{2}\, I \cos\omega t$,

Then $\upsilon(t) = \sqrt{2}|\bar{Z}|I\cos(\omega t + \angle\bar{Z})$

$\therefore p(t) = \upsilon(t) \cdot i(t) = |\bar{Z}|I^2 \cos(\omega t + \angle\bar{Z}) \cdot \cos\omega t$

$= |\bar{Z}|I^2\left[\cos\angle\bar{Z} + \cos(2\omega t + \angle\bar{Z})\right]$

$= |\bar{Z}|I^2\left[\cos\angle\bar{Z} + \cos 2\omega t \cos\angle\bar{Z} - \sin 2\omega t \sin\angle\bar{Z}\right]$

$= P(1 + \cos 2\omega t) - Q\sin 2\omega t$ ←

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

(c) $\bar{Z} = R + j\omega L + \dfrac{1}{j\omega C}$

From part (*a*), $P = RI^2$ and $Q = Q_L + Q_C$

where $Q_L = \omega L I^2$ and $Q_C = -\dfrac{1}{\omega C} I^2$

which are the reactive powers into L and C, respectively.

Thus $p(t) = P\left(1 + \cos 2\omega t\right) - Q_L \sin 2\omega t - Q_C \sin 2\omega t$ ←

If $\omega^2 LC = 1$, $Q_L + Q_C = Q = 0$


Then $p(t) = P\left(1 + \cos 2\omega t\right)$ ←

2.19 (a) $\bar{S} = \bar{V}\bar{I}^* = \left(\dfrac{150}{\sqrt{2}}\angle 10°\right)\left(\dfrac{5}{\sqrt{2}}\angle -50°\right)^* = 375\angle 60°$

$= 187.5 + j324.8$

$P = \text{Re}\,\bar{S} = 187.5\,\text{W Absorbed}$

$Q = \text{Im}\,\bar{S} = 324.8\,\text{VAR S Absorbed}$



(b) $pf = \cos(60°) = 0.5$ Lagging

(c) $Q_S = P\tan Q_S = 187.5\tan\left[\cos^{-1} 0.9\right] = 90.81\,\text{VAR S}$

$Q_C = Q_L - Q_S = 324.8 - 90.81 = 234\,\text{VAR S}$

2.20 $\bar{Y}_1 = \dfrac{1}{\bar{Z}_1} = \dfrac{1}{20\angle 30°} = 0.05\angle -30° = \left(0.0433 - j0.025\right)\text{S} = G_1 - jB_1$


$\bar{Y}_2 = \dfrac{1}{\bar{Z}_2} = \dfrac{1}{25\angle 60°} = 0.04\angle -60° = \left(0.02 - j0.03464\right)\text{S} = G_2 + jB_2$


$P_1 = V^2 G_1 = (100)^2\, 0.0433 = 433\,\text{W Absorbed}$


$Q_1 = V^2 B_1 = (100)^2\, 0.025 = 250\,\text{VAR S Absorbed}$

$P_2 = V^2 G_2 = (100)^2\, 0.02 = 200\,\text{W Absorbed}$

$Q_2 = V^2 B_2 = (100)^2\, 0.03464 = 346.4\,\text{VAR S Absorbed}$








© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

2.21 (a)



$$Q_L = P\tan\phi_L = 500\tan 53.13° = 666.7 \text{ kVAR}$$


$$\phi_S = \cos^{-1} 0.9 = 25.84°$$

$$Q_S = P\tan\phi_S = 500\tan 25.84° = 242.2\,\text{kVAR}$$

$$Q_C = Q_L - Q_S = 666.7 - 242.2 = 424.5\,\text{kVAR}$$

$$S_C = Q_C = 424.5\,\text{kVA}$$

(b) The Synchronous motor absorbs $P_m = \dfrac{(500)0.746}{0.9} = 414.4\,\text{kW}$ and $Q_m = 0\,\text{kVAR}$



$$\text{Source PF} = \cos\left[\tan^{-1}\left(666.7/914.4\right)\right] = 0.808 \text{ Lagging}$$

2.22 (a) $$\overline{Y}_1 = \frac{1}{\overline{Z}_1} = \frac{1}{(4+j5)} = \frac{1}{6.4\angle 51.34°} = 0.16\angle -51.34°$$

$$= (0.1 - j0.12)\text{S}$$

$$\overline{Y}_2 = \frac{1}{\overline{Z}_2} = \frac{1}{10} = 0.1\text{S}$$

$$P = V^2(G_1 + G_2) \Rightarrow V = \sqrt{\frac{P}{G_1 + G_2}} = \sqrt{\frac{1000}{(0.1+0.1)}} = 70.71 \text{ V}$$

$$P_1 = V^2 G_1 = (70.71)^2\, 0.1 = 500\,\text{W}$$

$$P_2 = V^2 G_2 = (70.71)^2\, 0.1 = 500\,\text{W}$$

(b) $$\overline{Y}_{eq} = \overline{Y}_1 + \overline{Y}_2 = (0.1 - j0.12) + 0.1 = 0.2 - j0.12$$

$$= 0.233\angle -30.96° \text{ S}$$

$$I_S = V\, Y_{eq} = 70.71(0.233) = 16.48\,\text{A}$$

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

2.23 $\overline{S} = \overline{V}\,\overline{I}^{\,*} = (120\angle 0°)(15\angle -30°) = 1800\angle -30°$

$= 1558.85 - j900$

$P = \text{Re}\,\overline{S} = 1558.85\,\text{W Delivered}$

$Q = \text{Im}\,\overline{S} = -900\,\text{VAR S Delivered} = +900\,\text{VAR S Absorbed}$

2.24 $\overline{S}_1 = P_1 + jQ_1 = 10 + j0;\ \overline{S}_2 = 10\angle \cos^{-1} 0.9 = 9 + j4.359$


$$\overline{S}_3 = \frac{10 \times 0.746}{0.85 \times 0.95}\angle -\cos^{-1} 0.95 = 9.238\angle -18.19° = 8.776 - j2.885$$

$\overline{S}_S = \overline{S}_1 + \overline{S}_2 + \overline{S}_3 = 27.78 + j1.474 = 27.82\angle 3.04°$

$P_S = \text{Re}(\overline{S}_S) = 27.78\,\text{kW}$

$Q_S = \text{Im}(\overline{S}_S) = 1.474\,\text{kVAR}$

$S_S = |\overline{S}_S| = 27.82\,\text{kVA}$




2.25 $\overline{S}_R = \overline{V}_R\overline{I}^{\,*} = R\overline{I}\,\overline{I}^{\,*} = I^2R = (20)^2 3 = 1200 + j0$

$\overline{S}_L = \overline{V}_L\overline{I}^{\,*} = (jX_L\overline{I})\overline{I}^{\,*} = jX_L I^2 = j8(20)^2 = 0 + j3200$

$\overline{S}_C = \overline{V}_C\overline{I}^{\,*} = (-j\overline{I}X_C)\overline{I}^{\,*} = -jX_C I^2 = -j4(20)^2 = 0 - j1600$

Complex power absorbed by the total load $\overline{S}_{LOAD} = \overline{S}_R + \overline{S}_L + \overline{S}_C = 2000\angle 53.1°$

Power Triangle:




Complex power delivered by the source is

$\overline{S}_{SOURCE} = \overline{V}\,\overline{I}^{\,*} = (100\angle 0°)(20\angle -53.1°)^* = 2000\angle 53.1°$

The complex power delivered by the source is equal to the total complex power absorbed by the load.

2.26 (a) The problem is modeled as shown in figure below:



$P_L = 120\,\text{kW}$

$pf_L = 0.85\,\text{Lagging}$


$\theta_L = \cos^{-1} 0.85 = 31.79°$

Power triangle for the load:

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

$$\overline{S}_L = P_L + jQ_L = 141.18\angle 31.79°\,\text{kVA}$$
$$I = S_L / V = 141{,}180/480 = 294.13\,\text{A}$$



$$Q_L = P_L \tan(31.79°) = 74.364\,\text{kVAR}$$

Real power loss in the line is zero.

Reactive power loss in the line is $Q_{LINE} = I^2 X_{LINE} = (294.13)^2\,1$
$= 86.512\,\text{kVAR}$

$$\therefore \overline{S}_S = P_S + jQ_S = 120 + j(74.364 + 86.512) = 200.7\angle 53.28°\,\text{kVA}$$


The input voltage is given by $V_S = S_S / I = 682.4\,\text{V (rms)}$

The power factor at the input is $\cos 53.28° = 0.6$ Lagging

(b) Applying KVL, $\overline{V}_S = 480\angle 0° + j1.0(294.13\angle -31.79°)$
$= 635 + j250 = 682.4\angle 21.5°\,\text{V (rms)}$

$(pf)_S = \cos(21.5° + 31.79°) = 0.6$ Lagging

2.27 The circuit diagram is shown below:



$$P_{old} = 50\,\text{kW};\ \cos^{-1} 0.8 = 36.87°;\ \theta_{OLD} = 36.87°;\ Q_{old} = P_{old}\tan(\theta_{old})$$
$$= 37.5\,\text{kVAR}$$

$$\therefore \overline{S}_{old} = 50{,}000 + j37{,}500$$

$$\theta_{new} = \cos^{-1} 0.95 = 18.19°;\ \overline{S}_{new} = 50{,}000 + j50{,}000\tan(18.19°)$$
$$= 50{,}000 + j16{,}430$$

Hence $\overline{S}_{cap} = \overline{S}_{new} - \overline{S}_{old} = -j21{,}070\,\text{VA}$

$$\therefore C = \frac{21{,}070}{(377)(220)^2} = 1155\mu\text{F} \quad \leftarrow$$

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

2.28 $\overline{S}_1 = 15 + j6.667$

$\overline{S}_2 = 3(0.96) - j3\left[\sin\left(\cos^{-1} 0.96\right)\right] = 2.88 - j0.84$

$\overline{S}_3 = 15 + j0$

$\overline{S}_{TOTAL} = \overline{S}_1 + \overline{S}_2 + \overline{S}_3 = (32.88 + j5.827)\text{kVA}$

(i) Let $\overline{\overline{Z}}$ be the impedance of a series combination of R and X

Since $\overline{S} = \overline{V}\,\overline{I}^* = \overline{V}\left(\dfrac{\overline{V}}{\overline{\overline{Z}}}\right)^* = \dfrac{V^2}{\overline{\overline{Z}}^*}$, it follows that

$$\overline{\overline{Z}}^* = \frac{V^2}{\overline{S}} = \frac{(240)^2}{(32.88 + j5.827)10^3} = (1.698 - j0.301)\,\Omega$$

$$\therefore \overline{\overline{Z}} = (1.698 + j0.301)\Omega \quad \leftarrow$$

(ii) Let $\overline{\overline{Z}}$ be the impedance of a parallel combination of R and X

Then $$R = \frac{(240)^2}{(32.88)10^3} = 1.7518\,\Omega$$

$$X = \frac{(240)^2}{(5.827)10^3} = 9.885\,\Omega$$

$$\therefore \overline{\overline{Z}} = (1.7518 \| j9.885)\,\Omega \quad \leftarrow$$

2.29 Since complex powers satisfy KCL at each bus, it follows that

$$\overline{S}_{13} = (1 + j1) - (1 - j1) - (0.4 + j0.2) = -0.4 + j1.8 \quad \leftarrow$$

$$\overline{S}_{31} = -\overline{S}_{13}^* = 0.4 + j1.8 \quad \leftarrow$$

Similarly, $\overline{S}_{23} = (0.5 + j0.5) - (1 + j1) - (-0.4 + j0.2) = -0.1 - j0.7 \quad \leftarrow$

$$\overline{S}_{32} = -\overline{S}_{23}^* = 0.1 - j0.7 \quad \leftarrow$$

At Bus 3, $\overline{S}_{G3} = \overline{S}_{31} + \overline{S}_{32} = (0.4 + j1.8) + (0.1 - j0.7) = 0.5 + j1.1 \quad \leftarrow$

2.30 (a) For load 1: $\theta_1 = \cos^{-1}(0.28) = 73.74°$ Lagging

$\overline{S}_1 = 125\angle 73.74° = 35 + j120$

$\overline{S}_2 = 10 - j40$

$\overline{S}_3 = 15 + j0$

$\overline{S}_{TOTAL} = \overline{S}_1 + \overline{S}_2 + \overline{S}_3 = 60 + j80 = 100\angle 53.13°\,\text{kVA} = P + jQ$

$\therefore P_{TOTAL} = 60\,\text{kW};\ Q_{TOTAL} = 80\,\text{kVAR};\ \text{kVA}_{TOTAL} = S_{TOTAL} = 100\,\text{kVA}. \quad \leftarrow$

Supply $pf = \cos(53.13°) = 0.6$ Lagging $\quad \leftarrow$

(b) $\overline{I}_{TOTAL} = \dfrac{\overline{S}^*}{\overline{V}^*} = \dfrac{100 \times 10^3 \angle -53.13°}{1000\angle 0°} = 100\angle -53.13°\,\text{A}$

At the new pf of 0.8 lagging, P_{TOTAL} of 60kW results in the new reactive power Q', such that

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

$$\theta' = \cos^{-1}(0.8) = 36.87°$$

and $Q' = 60\tan(36.87°) = 45\,\text{kVAR}$

$\therefore$ The required capacitor's kVAR is $Q_C = 80 - 45 = 35\,\text{kVAR}$ ←

It follows then $X_C = \dfrac{V^2}{\overline{S}_C^*} = \dfrac{(1000)^2}{j35000} = -j28.57\,\Omega$

and $$C = \frac{10^6}{2\pi(60)(28.57)} = 92.85\mu\text{F} \quad \leftarrow$$

The new current is $I' = \dfrac{\overline{S}'^*}{\overline{V}^*} = \dfrac{60{,}000 - j45{,}000}{1000\angle 0°} = 60 - j45 = 75\angle -36.87°\,\text{A}$

The supply current, in magnitude, is reduced from 100A to 75A ←

2.31 (a) $\overline{I}_{12} = \dfrac{V_1\angle\delta_1 - V_2\angle\delta_2}{X\angle 90°} = \left(\dfrac{V_1}{X}\angle\delta_1 - 90°\right) - \dfrac{V_2}{X}\angle\delta_2 - 90°$

Complex power $\overline{S}_{12} = \overline{V}_1\overline{I}_{12}^* = V_1\angle\delta_1\left[\dfrac{V_1}{X}\angle 90° - \delta_1 - \dfrac{V_2}{X}\angle 90° - \delta_2\right]$

$$= \frac{V_1^2}{X}\angle 90° - \frac{V_1V_2}{X}\angle 90° + \delta_1 - \delta_2$$

$\therefore$ The real and reactive power at the sending end are

$$P_{12} = \frac{V_1^2}{X}\cos 90° - \frac{V_1V_2}{X}\cos(90° + \delta_1 - \delta_2)$$

$$= \frac{V_1V_2}{X}\sin(\delta_1 - \delta_2) \quad \leftarrow$$

$$Q_{12} = \frac{V_1^2}{X}\sin 90° - \frac{V_1V_2}{X}\sin(90° + \delta_1 - \delta_2)$$

$$= \frac{V_1}{X}\left[V_1 - V_2\cos(\delta_1 - \delta_2)\right] \quad \leftarrow$$

Note: If $\overline{V}_1$ leads $\overline{V}_2$, $\delta = \delta_1 - \delta_2$ is positive and the real power flows from node 1 to node 2. If $\overline{V}_1$ Lags $\overline{V}_2$, δ is negative and power flows from node 2 to node 1.

(b) Maximum power transfer occurs when $\delta = 90° = \delta_1 - \delta_2$ ←

$$P_{\text{MAX}} = \frac{V_1V_2}{X} \quad \leftarrow$$

2.32 4 Mvar minimizes the real power line losses, while 4.5 Mvar minimizes the MVA power flow into the feeder.

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.


Power System Analysis and Design 6th edition Glover Solutions Manual

2.33

Qcap	MW Losses	Mvar Losses
0	0.42	0.84
0.5	0.4	0.8
1	0.383	0.766
1.5	0.369	0.738
2	0.357	0.714
2.5	0.348	0.696
3	0.341	0.682
3.5	0.337	0.675
4	0.336	0.672
4.5	0.337	0.675
5	0.341	0.682
5.5	0.348	0.696
6	0.357	0.714
6.5	0.369	0.738
7	0.383	0.766
7.5	0.4	0.801
8	0.42	0.84
8.5	0.442	0.885
9	0.467	0.934
9.5	0.495	0.99
10	0.525	1.05

2.34 7.5 Mvars

2.35



(Admittance values are shown)

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

$$\left[\begin{array}{c|c} (.3846+.4950)+j(10-1.923-4.950) & -(.4950-j4.950) \\ \hline -(.4950-j4.950) & (.3846+.4950)+j(10-1.923-4.95) \end{array}\right]\left[\begin{array}{c}\bar{V}_{10}\\ \bar{V}_{20}\end{array}\right]$$

$$=\left[\begin{array}{c}1.961\angle -48.69^\circ\\ 1.961\angle -78.69^\circ\end{array}\right]$$

$$\left[\begin{array}{c|c} 0.8796+j3.127 & -0.4950+j4.950 \\ \hline -0.4950+j4.950 & -0.8796+j3.127 \end{array}\right]\left[\begin{array}{c}\bar{V}_{10}\\ \bar{V}_{20}\end{array}\right]=\left[\begin{array}{c}1.961\angle -48.69^\circ\\ 1.961\angle -78.69^\circ\end{array}\right]$$

2.36 Note that there are two buses plus the reference bus and one line for this problem. After converting the voltage sources in Fig. 2.29 to current sources, the equivalent source impedances are:

$$\bar{Z}_{S1}=\bar{Z}_{S2}=(0.1+j0.5)//(-j0.1)=\frac{(0.1+j0.5)(-j0.1)}{0.1+j0.5-j0.1}$$

$$=\frac{(0.5099\angle 78.69^\circ)(0.1\angle -90^\circ)}{0.4123\angle 75.96^\circ}=0.1237\angle -87.27^\circ$$

$$=0.005882-j0.1235\,\Omega$$

The rest is left as an exercise to the student.

2.37 After converting impedance values in Figure 2.30 to admittance values, the bus admittance matrix is:

$$\bar{Y}_{bus}=\left[\begin{array}{cccc} 1 & -1 & 0 & 0 \\ -1 & \left(1+\frac{1}{2}+\frac{1}{3}+\frac{1}{4}-j1\right) & -\left(\frac{1}{3}-j1\right) & -\left(\frac{1}{4}\right) \\ 0 & -\left(\frac{1}{3}-j1\right) & \left(\frac{1}{3}-j1+j\frac{1}{4}+j\frac{1}{2}\right) & -\left(j\frac{1}{4}\right) \\ 0 & -\left(\frac{1}{4}\right) & -\left(j\frac{1}{4}\right) & \left(\frac{1}{4}+j\frac{1}{4}-j\frac{1}{3}\right) \end{array}\right]$$


Writing nodal equations by inspection:

$$\left[\begin{array}{cccc} 1 & -1 & 0 & 0 \\ -1 & (2.083-j1) & (-0.3333+j1) & -0.25 \\ 0 & (-0.3333+j1) & (0.3333-j0.25) & -j0.25 \\ 0 & (-0.25) & -j0.25 & (0.25-j0.08333) \end{array}\right]\left[\begin{array}{c}\bar{V}_{10}\\ \bar{V}_{20}\\ \bar{V}_{30}\\ \bar{V}_{40}\end{array}\right]=\left[\begin{array}{c}1\angle 0^\circ\\ 0\\ 0\\ 2\angle 30^\circ\end{array}\right]$$

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

2.38 The admittance diagram for the system is shown below:



$$\bar{Y}_{BUS} = \begin{bmatrix} \bar{Y}_{11} & \bar{Y}_{12} & \bar{Y}_{13} & \bar{Y}_{14} \\ \bar{Y}_{21} & \bar{Y}_{22} & \bar{Y}_{23} & \bar{Y}_{24} \\ \bar{Y}_{31} & \bar{Y}_{32} & \bar{Y}_{33} & \bar{Y}_{34} \\ \bar{Y}_{41} & \bar{Y}_{42} & \bar{Y}_{43} & \bar{Y}_{44} \end{bmatrix} = j \begin{bmatrix} -8.5 & 2.5 & 5.0 & 0 \\ 2.5 & -8.75 & 5.0 & 0 \\ 5.0 & 5.0 & -22.5 & 12.5 \\ 0 & 0 & 12.5 & -12.5 \end{bmatrix} S$$

where $\bar{Y}_{11} = \bar{y}_{10} + \bar{y}_{12} + \bar{y}_{13}; \bar{Y}_{22} = \bar{y}_{20} + \bar{y}_{12} + \bar{y}_{23}; \bar{Y}_{23} = \bar{y}_{13} + \bar{y}_{23} + \bar{y}_{34}$

$\bar{Y}_{44} = y_{34}; \bar{Y}_{12} = \bar{Y}_{21} = -\bar{y}_{12}; \bar{Y}_{13} = \bar{Y}_{31} = -\bar{y}_{13}; \bar{Y}_{23} = \bar{Y}_{32} = -\bar{y}_{23}$

and $\bar{Y}_{34} = \bar{Y}_{43} = -\bar{y}_{34}$

2.39 (a)

$$\begin{bmatrix} \bar{Y}_c + \bar{Y}_d + \bar{Y}_f & -\bar{Y}_d & -\bar{Y}_c & -\bar{Y}_f \\ -\bar{Y}_d & \bar{Y}_b + \bar{Y}_d + \bar{Y}_e & -\bar{Y}_b & -\bar{Y}_e \\ -\bar{Y}_c & -\bar{Y}_b & \bar{Y}_a + \bar{Y}_b + \bar{Y}_c & 0 \\ -\bar{Y}_f & -\bar{Y}_e & 0 & \bar{Y}_e + \bar{Y}_f + \bar{Y}_g \end{bmatrix} \begin{bmatrix} \bar{V}_1 \\ \bar{V}_2 \\ \bar{V}_3 \\ \bar{V}_4 \end{bmatrix} = \begin{bmatrix} \bar{I}_1 = 0 \\ \bar{I}_2 = 0 \\ \bar{I}_3 \\ \bar{I}_4 \end{bmatrix}$$

(b) $$j \begin{bmatrix} -14.5 & 8 & 4 & 2.5 \\ 8 & -17 & 4 & 5 \\ 4 & 4 & -8.8 & 0 \\ 2.5 & 5 & 0 & -8.3 \end{bmatrix} \begin{bmatrix} \bar{V}_1 \\ \bar{V}_2 \\ \bar{V}_3 \\ \bar{V}_4 \end{bmatrix} = \begin{bmatrix} 0 \\ 0 \\ 1\angle -90° \\ 0.62\angle -135° \end{bmatrix}$$

$$\bar{Y}_{BUS}\,\bar{V} = \bar{I}; \bar{Y}_{BUS}^{-1}\,\bar{Y}_{BUS}\,\bar{V} = \bar{Y}_{BUS}^{-1}\bar{I}$$

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

where $\bar{Y}_{BUS}^{-1} = \bar{Z}_{BUS} = j\begin{bmatrix} 0.7187 & 0.6688 & 0.6307 & 0.6194 \\ 0.6688 & 0.7045 & 0.6242 & 0.6258 \\ 0.6307 & 0.7045 & 0.6840 & 0.5660 \\ 0.6194 & 0.6258 & 0.5660 & 0.6840 \end{bmatrix} \Omega$

$$\bar{V} = \bar{Y}_{BUS}^{-1}\,\bar{I}$$

where $\bar{V} = \begin{bmatrix} \bar{V}_1 \\ \bar{V}_2 \\ \bar{V}_3 \\ \bar{V}_4 \end{bmatrix}$ and $\bar{I} = \begin{bmatrix} 0 \\ 0 \\ 1\angle -90^\circ \\ 0.62\angle -135^\circ \end{bmatrix}$

Then solve for $\bar{V}_1$, $\bar{V}_2$, $\bar{V}_3$, and $\bar{V}_4$.

2.40 (a) $\bar{V}_{AN} = \dfrac{240}{\sqrt{3}}\angle 0^\circ = 138.56\angle 0^\circ \text{ V}$ (Assumed as Reference)

$$\bar{V}_{AB} = 240\angle 30^\circ \text{ V}; \bar{V}_{BC} = 240\angle -90^\circ \text{ V}; \bar{I}_A = 15\angle -90^\circ \text{ A}$$

$$\bar{Z}_Y = \frac{\bar{V}_{AN}}{\bar{I}_A} = \frac{138.56\angle 0^\circ}{15\angle -90^\circ} = 9.24\angle 90^\circ = (0 + j9.24)\,\Omega$$

(b) $\bar{I}_{AB} = \dfrac{\bar{I}_A}{\sqrt{3}}\angle 30^\circ = \dfrac{15}{\sqrt{3}}\angle -90^\circ + 30^\circ = 8.66\angle -60^\circ \text{A}$

$$\bar{Z}_\Delta = \frac{\bar{V}_{AB}}{\bar{I}_{AB}} = \frac{240\angle 30^\circ}{8.66\angle -60^\circ} = 27.71\angle 90^\circ = (0 + j27.71)\,\Omega$$

Note: $\bar{Z}_Y = \bar{Z}_\Delta / 3$

2.41 $\bar{S}_{3\phi} = \sqrt{3}V_{LL}\,I_L\angle \cos^{-1}(pf)$


$$= \sqrt{3}\,(480)(20)\angle \cos^{-1} 0.8$$

$$= 16.627\times 10^3 \angle 36.87^\circ$$


$$= (13.3\times 10^3) + j(9.976\times 10^3)$$

$P_{3\phi} = \text{Re}\,\bar{S}_{3\phi} = 13.3\,\text{kW}$ Delivered

$Q_{3\phi} = I_m \bar{S}_{3\phi} = 9.976\,\text{kVAR}$ Delivered



2.42 (a) With $\bar{V}_{ab}$ as reference



$$\bar{V}_{an} = \frac{208}{\sqrt{3}}\angle -30^\circ \qquad \frac{\bar{Z}_\Delta}{3} = 4 + j3 = 5\angle 36.87^\circ\,\Omega$$

$$\bar{I}_a = \frac{\bar{V}_{an}}{(\bar{Z}_\Delta / 3)} = \frac{120.1\angle -30^\circ}{5\angle 36.87^\circ} = 24.02\angle -66.87^\circ \text{ A}$$

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.


Power System Analysis and Design 6th edition Glover Solutions Manual

$$\bar{S}_{3\phi} = 3\bar{V}_{an}\bar{I}_a^* = 3\left(120.1\angle -30°\right)\left(24.02\angle +66.87°\right)$$
$$= 8654\angle 36.87° = 6923 + j5192$$

$P_{3\phi} = 6923\,\text{W}; Q_{3\phi} = 5192\,\text{VAR}$; both absorbed by the load

$pf = \cos(36.87°) = 0.8$ Lagging; $S_{3\phi} = \left|\bar{S}_{3\phi}\right| = 8654\,\text{VA}$

(b)




$\bar{V}_{ab} = 208\angle 0°\,\text{V}$ $\bar{I}_a = 24.02\angle -66.87°\,\text{A}$ $13.87\angle -36.87°\,\text{A}$

2.43 (a) Transforming the Δ-connected load into an equivalent *Y*, the impedance per phase of the equivalent *Y* is

$$\bar{Z}_2 = \frac{60 - j45}{3} = (20 - j15)\,\Omega$$

With the phase voltage $V_1 = \frac{120\sqrt{3}}{\sqrt{3}} = 120\,\text{V}$ taken as a reference, the per-phase equivalent circuit is shown below:



Total impedance viewed from the input terminals is

$$\bar{Z} = 2 + j4 + \frac{(30 + j40)(20 - j15)}{(30 + j40) + (20 - j15)} = 2 + j4 + 22 - j4 = 24\,\Omega$$

$$\bar{I} = \frac{\bar{V}_1}{\bar{Z}} = \frac{120\angle 0°}{24} = 5\angle 0°\,\text{A}$$

The three-phase complex power supplied = $\bar{S} = 3\bar{V}_1\,\bar{I}^* = 1800\,\text{W}$

$P = 1800\,\text{W}$ and $Q = 0\,\text{VAR}$ delivered by the sending-end source

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

(b) Phase voltage at load terminals $\bar{V}_2 = 120\angle 0° - (2 + j4)(5\angle 0°)$

$$= 110 - j20 = 111.8\angle -10.3° \text{ V}$$

The line voltage magnitude at the load terminal is

$$(V_{\text{LOAD}})_{L\text{-}L} = \sqrt{3}\, 111.8 = 193.64 \text{ V}$$

(c) The current per phase in the Y-connected load and in the equiv. Y of the Δ-load:

$$\bar{I}_1 = \frac{\bar{V}_2}{\bar{Z}_1} = 1 - j2 = 2.236\angle -63.4° \text{ A}$$

$$\bar{I}_2 = \frac{\bar{V}_2}{\bar{Z}_2} = 4 + j2 = 4.472\angle 26.56° \text{ A}$$

The phase current magnitude in the original Δ-connected load

$$(I_{ph})_{\Delta} = \frac{I_2}{\sqrt{3}} = \frac{4.472}{\sqrt{3}} = 2.582 \text{ A}$$

(d) The three-phase complex power absorbed by each load is

$$\bar{S}_1 = 3\bar{V}_2\bar{I}_1^* = 430 \text{ W} + j600 \text{ VAR}$$

$$\bar{S}_2 = 3\bar{V}_2\bar{I}_2^* = 1200 \text{ W} - j900 \text{ VAR}$$

The three-phase complex power absorbed by the line is


$$\bar{S}_L = 3(R_L + jX_L)I^2 = 3(2 + j4)(5)^2 = 150 \text{ W} + j300 \text{ VAR}$$

The sum of load powers and line losses is equal to the power delivered from the supply:

$$\bar{S}_1 + \bar{S}_2 + \bar{S}_L = (450 + j600) + (1200 - j900) + (150 + j300)$$

$$= 1800 \text{ W} + j0 \text{ VAR}$$

2.44 (a) The per-phase equivalent circuit for the problem is shown below:



Phase voltage at the load terminals is $V_2 = \dfrac{2200\sqrt{3}}{\sqrt{3}} = 2200 \text{ V}$ taken as Ref.

Total complex power at the load end or receiving end is

$$\bar{S}_{R(3\phi)} = 560.1(0.707 + j0.707) + 132 = 528 + j396 = 660\angle 36.87° \text{ kVA}$$

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

With phase voltage $\overline{V}_2$ as reference,

$$\overline{I} = \frac{\overline{S}^*_{R(3\phi)}}{3\overline{V}^*_2} = \frac{660{,}000\angle -36.87^\circ}{3(2200\angle 0^\circ)} = 100\angle -36.87^\circ \text{ A}$$

Phase voltage at sending end is given by

$$\overline{V}_1 = 2200\angle 0^\circ + (0.4 + j2.7)(100\angle -36.87^\circ) = 2401.7\angle 4.58^\circ \text{ V}$$

The magnitude of the line to line voltage at the sending end of the line is

$$(V_1)_{L\text{-}L} = \sqrt{3}V_1 = \sqrt{3}(2401.7) = 4160 \text{ V}$$

(b) The three-phase complex-power loss in the line is given by


$$\overline{S}_{L(3\phi)} = 3RI^2 + j3 \times I^2 = 3(0.4)(100^2) + j3(2.7)(100)^2$$
$$= 12 \text{ kW} + j81 \text{ kVAR}$$

(c) The three-phase sending power is

$$\overline{S}_{S(3\phi)} = 3\overline{V}_1\overline{I}^* = 3(2401.7\angle 4.58^\circ)(100\angle 36.87^\circ)$$
$$= 540 \text{ kW} + j477 \text{ kVAR}$$

Note that $\overline{S}_{S(3\phi)} = \overline{S}_{R(3\phi)} + \overline{S}_{L(3\phi)}$


2.45 (a)



$$I_S = \frac{S_S}{\sqrt{3}V_{LL}} = \frac{25.001 \times 10^3}{\sqrt{3}(480)} = 30.07 \text{ A}$$

(b) The ammeter reads zero, because in a balanced three-phase system, there is no neutral current.

2.46 (a)



© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

Using voltage division: $\bar{V}_{AN} = \bar{V}_{an}\dfrac{\bar{Z}_\Delta/3}{(\bar{Z}_\Delta/3)+\bar{Z}_{LINE}}$


$$= \frac{208}{\sqrt{3}}\angle 0°\frac{10\angle 30°}{10\angle 30° + (0.8 + j0.6)}$$

$$= \frac{(120.09)(10\angle 30°)}{9.46 + j5.6} = \frac{1200.9\angle 30°}{10.99\angle 30.62°}$$

$$= 109.3\angle -0.62° \text{ V}$$

Load voltage = $V_{AB} = \sqrt{3}\,(109.3) = 189.3\,\text{V}$ Line-to-Line

(b)



$$\bar{Z}_{eq} = 10\angle 30° \,||\, (-j20)$$

$$= 11.547\angle 0°\Omega$$


$$\bar{V}_{AN} = \bar{V}_{an}\frac{\bar{Z}_{eq}}{\bar{Z}_{eq} + \bar{Z}_{LINE}}$$

$$= \left(208/\sqrt{3}\right)\frac{11.547}{(11.547 + 0.8 + j0.6)}$$

$$= \frac{1386.7}{12.362\angle 2.78°} = 112.2\angle -2.78° \text{ V}$$

Load voltage Line-to-Line $V_{AB} = \sqrt{3}\,(112.2) = 194.3$ V

2.47



(a) $\bar{I}_{G1} = \dfrac{15\times 10^3}{\sqrt{8}\,(460)(0.8)}\angle -\cos^{-1} 0.8 = 23.53\angle -36.87°\,\text{A}$

$$\bar{V}_L = \bar{V}_{G1} - \bar{Z}_{LINE1}\,\bar{I}_{G1} = \frac{460}{\sqrt{3}}\angle 0° - (1.4 + j1.6)(23.53\angle -36.87°)$$

$$= 216.9\angle -2.73° \text{ V Line to Neutral}$$

Load Voltage $V_L = \sqrt{3}\,216.9 = 375.7\,\text{V}$ Line to line

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

(b) $\bar{I}_L = \dfrac{30\times10^3}{\sqrt{3}(375.7)(0.8)}\angle -2.73° - \cos^{-1}0.8 = 57.63\angle -39.6°\ \text{A}$

$\bar{I}_{G2} = \bar{I}_L - \bar{I}_{G1} = 57.63\angle -39.6° - 23.53\angle -36.87°$

$= 34.14\angle -41.49°\ \text{A}$

$\bar{V}_{G2} = \bar{V}_L + \bar{Z}_{LINE2}\ \bar{I}_{G2} = 216.9\angle -2.73° + (0.8 + j1)(34.14\angle -41.49°)$

$= 259.7\angle -0.63°\ \text{V}$

Generator 2 line-to-line voltage $V_{G2} = \sqrt{3}(259.7)$


$= 449.8\ \text{V}$

(c) $\bar{S}_{G2} = 3\bar{V}_{G2}\ \bar{I}_{G_2^*} = 3(259.7\angle -0.63°)(34.14\angle 41.49°)$

$= 20.12\times10^3 + j17.4\times10^3$

$P_{G2} = 20.12\ \text{kW};\ Q_{G2} = 17.4\ \text{kVAR};$ Both delivered

2.48 (a)



(b) $pf = \cos 31.32° = 0.854$ Lagging

(c) $I_L = \dfrac{S_L}{\sqrt{3}V_{LL}} = \dfrac{26.93\times10^3}{\sqrt{3}(480)} = 32.39\ \text{A}$

(d) $Q_C = Q_L = 14\times10^3\ \text{VAR} = 3(V_{LL})^2 / X_\Delta$

$X_\Delta = \dfrac{3(480)^2}{14\times10^3} = 49.37\ \Omega$

(e) $I_C = V_{LL} / X_\Delta = 480 / 49.37 = 9.72\ \text{A}$

$I_{LINE} = \dfrac{P_L}{\sqrt{3}\ V_{LL}} = \dfrac{23\times10^3}{\sqrt{3}\ 480} = 27.66\ \text{A}$

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

2.49 (a) Let $\bar{Z}_Y = \bar{Z}_A = \bar{Z}_B = \bar{Z}_C$ for a balanced Y-load

$$\bar{Z}_\Delta = \bar{Z}_{AB} = \bar{Z}_{BC} = \bar{Z}_{CA}$$

Using equations in Fig. 2.27

$$\bar{Z}_\Delta = \frac{\bar{Z}_Y^2 + \bar{Z}_Y^2 + \bar{Z}_Y^2}{\bar{Z}_Y} = 3\bar{Z}_Y$$

and


$$\bar{Z}_Y = \frac{\bar{Z}_\Delta^2}{\bar{Z}_\Delta + \bar{Z}_\Delta + \bar{Z}_\Delta} = \frac{\bar{Z}_\Delta}{3}$$

(b) $\bar{Z}_A = \dfrac{(j10)(-j25)}{j10 + j20 - j25} = -j\,50\ \Omega$

$$\bar{Z}_B = \frac{(j10)(j20)}{j5} = j\,40\ \Omega; \bar{Z}_C = \frac{(j20)(-j25)}{j5} = -j100\ \Omega$$

2.50 Replace delta by the equivalent WYE: $\bar{Z}_Y = -j\dfrac{2}{3}\ \Omega$

Per-phase equivalent circuit is shown below:



Noting that $\left(j1.0 \left\| -j\frac{2}{3}\right.\right) = -j\,2$, by voltage-divider law,

$$\bar{V}_1 = \frac{-j2}{-j2 + j0.1}(100\angle 0°) = 105\angle 0°$$

$$\therefore \upsilon_1(t) = 105\sqrt{2}\cos(\omega t + 0°) = 148.5\cos\omega t\ \text{V} \quad \leftarrow$$

In order to find $i_2(t)$ in the original circuit, let us calculate $\bar{V}_{A'B'}$

$$\bar{V}_{A'B'} = \bar{V}_{A'N'} - \bar{V}_{B'N'} = \sqrt{3}\,e^{j30°}\bar{V}_{A'N'} = 173.2\angle 30°$$

Then $$\bar{I}_{A'B'} = \frac{173.2\angle 30°}{-j2} = 86.6\angle 120°$$

$$\therefore i_2(t) = 86.6\sqrt{2}\cos(\omega t + 120°)$$

$$= 122.5\cos(\omega t + 120°)\,\text{A} \quad \leftarrow$$

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

2.51 On a per-phase basis $\bar{S}_1 = \frac{1}{3}(150 + j120) = (50 + j40)\,\text{kVA}$

$$\therefore \bar{I}_1 = \frac{(50 - j40)10^3}{2000} = (25 - j20)\,\text{A}$$

Note: PF Lagging

Load 2: Convert Δ into an equivalent Y

$$\bar{Z}_{2Y} = \frac{1}{3}(150 - j48) = (50 - j16)\,\Omega$$

$$\therefore \bar{I}_2 = \frac{2000\angle 0°}{50 - j16} = 38.1\angle 17.74°$$

$$= (36.29 + j11.61)\,\text{A}$$

Note: PF Leading

$\bar{S}_3$ per phase $= \frac{1}{3}\left[(120 \times 0.6) - j120\sin(\cos^{-1} 0.6)\right] = (24 - j32)\,\text{kVA}$

$$\therefore \bar{I}_3 = \frac{(24 + j32)10^3}{2000} = (12 + j16)\,\text{A}$$

Note: PF Leading

Total current drawn by the three parallel loads $\bar{I}_T = \bar{I}_1 + \bar{I}_2 + \bar{I}_3$

$$\bar{I}_{TOTAL} = (73.29 + j7.61)\,\text{A}$$

Note: PF Leading

Voltage at the sending end: $\bar{V}_{AN} = 2000\angle 0° + (73.29 + j7.61)(0.2 + j1.0)$

$$= 2007.05 + j74.81 = 2008.44\angle 2.13°\,\text{V}$$

Line-to-line voltage magnitude at the sending end $= \sqrt{3}(2008.44) = 3478.62\,\text{V}$ ←

2.52 (a) Let $\bar{V}_{AN}$ be the reference: $\bar{V}_{AN} = \frac{2160}{\sqrt{3}}\angle 0° \simeq 2400\angle 0°\,\text{V}$

Total impedance per phase $\bar{Z} = (4.7 + j9) + (0.3 + j1) = (5 + j10)\,\Omega$

$\therefore$ Line Current $= \frac{2400\angle 0°}{5 + j10} = 214.7\angle -63.4°\,\text{A} = \bar{I}_A$ ←

With positive A-B-C phase sequence,

$$\bar{I}_B = 214.7\angle -183.4°\,\text{A};\ \bar{I}_C = 214.7\angle -303.4° = 214.7\angle 56.6°\,\text{A}$$ ←

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

(b) $\left(\bar{V}_{A'N}\right)_{LOAD} = 2400\angle 0° - \left[\left(214.7\angle -63.4°\right)\left(0.3 + j1\right)\right]$

$= 2400\angle 0° - 224.15\angle 9.9° = 2179.2 - j38.54$

$= 2179.5\angle -1.01°\,\text{V} \quad \leftarrow$

$\left(\bar{V}_{B'N}\right)_{LOAD} = 2179.5\angle -121.01°\,\text{V}^{\square}; \left(V_{C'N}\right)_{LOAD} = 2179.5\angle -241.01°\,\text{V}^{\square}$

(c) $S/\text{Phase} = \left(V_{A'N}\right)_{LOAD} I_A = \left(2179.5\right)\left(214.7\right) = 467.94\,\text{kVA} \quad \leftarrow$

Total apparent power dissipated in all three phases in the load

$$\left[S_{3\phi}\right]_{LOAD} = 3\left(467.94\right) = 1403.82\,\text{kVA} \quad \leftarrow$$

Active power dissipated per phase in load = $\left(P_{1\phi}\right)_{LOAD}$

$$= \left(2179.5\right)\left(214.7\right)\cos\left(62.39°\right) = 216.87\,\text{kW} \quad \leftarrow$$

$$\therefore \left[P_{3\phi}\right]_{LOAD} = 3\left(216.87\right) = 650.61\,\text{kW} \quad \leftarrow$$

Reactive power dissipated per phase in load = $\left(Q_{1\phi}\right)_{LOAD}$

$$= \left(2179.5\right)\left(214.7\right)\sin\left(62.39°\right) = 414.65\,\text{kVAR} \quad \leftarrow$$

$$\therefore \left[Q_{3\phi}\right]_{LOAD} = 3\left(414.65\right) = 1243.95\,\text{kVAR} \quad \leftarrow$$

(d) Line losses per phase $\left(P_{1\phi}\right)_{LOSS} = \left(214.7\right)^2 0.3 = 13.83\,\text{kW} \quad \leftarrow$

Total line loss $\left(P_{3\phi}\right)_{LOSS} = 13.83 \times 3 = 41.49\,\text{kW} \quad \leftarrow$

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual

© 2017 Cengage Learning®. May not be scanned, copied or duplicated, or posted to a publicly accessible website, in whole or in part.

Power System Analysis and Design 6th edition Glover Solutions Manual